

Aquarea LT Monoblöcke Generation „J“ Heizen und Kühlen MDC einphasig R32		Einphasig 7 kW
Outdoor unit		WH-MDC07J3E5
Heating capacity (A +7°C, W 35°C)	kW	7,00
COP (A +7°C, W 35°C)		4,76
Heating capacity (A +7°C, W 55°C)	kW	7,00
COP (A +7°C, W 55°C)		2,82
Heating capacity (A +2°C, W 35°C)	kW	7,00
COP (A +2°C, W 35°C)		3,40
Heating capacity (A +2°C, W 55°C)	kW	6,30
COP (A +2°C, W 55°C)		2,16
Heating capacity (A -7°C, W 35°C)	kW	6,80
COP (A -7°C, W 35°C)		2,81
Heating capacity (A -7°C, W 55°C)	kW	6,30
COP (A -7°C, W 55°C)		1,86
Cooling capacity (A 35°C, W 7°C)	kW	7,00
EER (A 35°C, W 7°C)		3,06
Cooling capacity (A 35°C, W 18°C)	kW	7,00
EER (A 35°C, W 18°C)		4,73
Heating average climate. Seasonal energy efficiency (W 35°C / W 55°C)	ηs %	193 / 130
Heating average climate. Seasonal energy efficiency (W 35°C / W 55°C)	SCOP	4,90 / 3,32
Heating average climate. Energy class (W 35°C / W 55°C) (1)	A+++ to D	A+++ / A++
Heating warm climate. Seasonal energy efficiency (W 35°C / W 55°C)	ηs %	227 / 160
Heating warm climate. Seasonal energy efficiency (W 35°C / W 55°C)	SCOP	5,75 / 4,07
Heating warm climate. Energy class (W 35°C / W 55°C) (1)	A+++ to D	A+++ / A+++
Heating cold climate. Seasonal energy efficiency (W 35°C / W 55°C)	ηs %	164 / 116
Heating cold climate. Seasonal energy efficiency (W 35°C / W 55°C)	SCOP	4,18 / 2,98
Heating cold climate. Energy class (W 35°C / W 55°C) (1)	A+++ to D	A++ / A+
Outdoor sound power part load (Heat) (1)	dB(A)	59
Outdoor sound power full load (Heat)	dB(A)	68
Outdoor sound power full load (Cool)	dB(A)	67
Outdoor dimension (Height)	mm	865
Outdoor dimension (Width)	mm	1283
Outdoor dimension (Depth)	mm	320
Outdoor net weight	kg	104
Refrigerant (R32) / CO2 Eq. (2)	kg / T	1,3 / 0,878
Water pipe connector	Inch	R 1¼
Pump (Number of speeds)		Variable Speed
Pump (Input power Min)	W	36
Pump (Input power Max)	W	100
Heating water flow (ΔT=5 K, 35°C)	L/min	20,10
Capacity of integrated electric heater	kW	3,00
Input power (Heat)	kW	1,47
Input power (Cool)	kW	2,29
Running and starting current (Heat)	A	7,0
Running and starting current (Cool)	A	10,5
Current 1	A	17
Current 2	A	13
Indoor recommended fuse	A	30 / 15
Recommended cable size, supply 1	mm²	3 x 2,5
Recommended cable size, supply 2	mm²	3 x 1,5
Operation range - outdoor temperature (Heat)	°C	-20 ~ 35
Operation range - outdoor temperature (Cool)	°C	10 ~ 43
Water outlet (Heat)	°C	20 ~ 60
Water outlet (Cool)	°C	5 ~ 20

1) Schallleistungspegel des Außengeräts bei A7/W55 gemäß EU-Verordnungen 811/2013 und 813/2013 sowie EN12102-1:2017.

2) WH-MDC-Modelle sind hermetisch abgeschlossen.

EER-/COP-Werte werden in Übereinstimmung mit EN14511 berechnet.

Zubehör